

<b>Evans</b> <b>CAPACITOR</b> <b>Company</b>	<b>Product Specification</b> <b>HYBRID<sup>®</sup> CAPACITOR</b>	<b>NUMBER</b>	<b>HQ1</b>
		<b>ISSUE</b>	<b>01</b>
		<b>REVISION</b>	<b>D (04-005)</b>
		<b>DATE</b>	<b>2/24/04</b>

**1.0 Scope**

This document contains specific electrical, mechanical, and environmental requirements and specifications for HQ1 series polymer case Hybrid<sup>®</sup> Capacitors. These specifications are subject to change without notice.

**2.0 Construction**

**2.1 General**

The capacitor shall utilize sintered tantalum anodes and ruthenium oxide coated cathodes operating in aqueous electrolyte. The components shall be sealed in a polymer case.

**2.2 Package**

The configuration and dimensions shall be as per Figure 1.

**2.3 Mass**

0-50 volt parts: 25± 3grams; 63-125 volt parts: 31 ± 3 grams.

**2.4 Part Markings**

The capacitor shall be permanently and legibly labeled on the case with the following information.

- i. Manufacturer's name and cage code
- ii. Manufacturer's part identification number
- iii. Capacitance
- iv. Working voltage
- v. Date/lot code
- vi. Polarity

**2.5 Solderability**

The terminations shall be solderable per ANSI J-STD-002.

**2.6 Resistance To Soldering Heat**

The capacitor must withstand solder dipping of the terminals at 260°C for 10 seconds per MIL-STD-202, Method 210, Condition B. The capacitor must not be visibly damaged and the electrical characteristics must not be affected.

**3.0 Environmental Requirements**

**3.1 Operating Temperature**

-40°C to +70°C.

**3.2 Storage Temperature**

-40°C to +80°C

**4.0 Electrical Requirements**

**4.1 Capacitance**

The capacitance is specified in Table 2 at 120 Hz and 25°C, ± 20%.

#### 4.2 Working Voltage

The working voltage rating is from 0 to V as specified in Table 2.

#### 4.4 Equivalent Series Resistance

The maximum equivalent series resistance (ESR) is specified in Table 2 at 1 kHz and 25°C.

#### 4.5 DC Leakage Current

The maximum DC leakage current is specified in Table 2 following 5 minutes at working voltage and 25°C.

**Table 2. Electrical Specifications**

V (VDC)	Capacitance	Part Number	Surge Voltage	DCL (max)	ESR (max)
6.3 V	75 000 $\mu$ F	HQ1006753	7.0 V	150 $\mu$ A	0.050 $\Omega$
8 V	60 000 $\mu$ F	HQ1008603	8.8 V	150 $\mu$ A	0.050 $\Omega$
10 V	53 000 $\mu$ F	HQ1010533	11 V	150 $\mu$ A	0.050 $\Omega$
16 V	36 000 $\mu$ F	HQ1016363	18 V	150 $\mu$ A	0.050 $\Omega$
25 V	23 000 $\mu$ F	HQ1025233	28 V	150 $\mu$ A	0.050 $\Omega$
35 V	12 000 $\mu$ F	HQ1035123	39 V	150 $\mu$ A	0.050 $\Omega$
50 V	8000 $\mu$ F	HQ1050802	55 V	170 $\mu$ A	0.060 $\Omega$
63 V	4000 $\mu$ F	HQ1063402	69 V	170 $\mu$ A	0.100 $\Omega$
80 V	2800 $\mu$ F	HQ1080282	88 V	200 $\mu$ A	0.100 $\Omega$
100 V	2100 $\mu$ F	HQ1100212	110 V	200 $\mu$ A	0.125 $\Omega$
110 V	1500 $\mu$ F	HQ1110152	127 V	200 $\mu$ A	0.200 $\Omega$
125 V	1100 $\mu$ F	HQ1125112	138 V	200 $\mu$ A	0.200 $\Omega$

**Figure 1. Part Sketch.**

